

Amateur Radio GT-5R PRO

FCC

User Manual

PREFACE

Thank you for purchasing this product. which is a dual band/dual display/dual watch. This easy-to-use radio will deliver you secure, instant and reliable communications at peak efficiency. Please read this manual carefully before use. The information presented herein will help you to derive maximum performance from your radio.



WARNING! European Users should note that operation of this unit in Transmit mode requires the operator to have a valid Amateur Radio License from their respective Countries Amateur Radio Licensing Authority for the Frequencies and Transmitter Power levels that this Radio transmits on. Failure to comply may be unlawful and liable for prosecution. At this subject, refer to the "EU" specification guide 2014/53/EU.



ATTENTION! When programming the radio, start by reading the factory software data, and then rewrite this data with your frequency etc., to a new saved code plug, otherwise errors may occur. You can use the programming cable with a PC to program the authorized frequency, bandwidth, power, etc. your programming must comply with your FCC (or EU other country) license certification.



ATTENTION! Before using this product, read the RF Energy Exposure and Product Safety Guide that ship with the radio which contains instructions for safe usage and RF energy awareness and control for compliance with applicable standards and regulation.



PMR446, FRS, GMRS, MURS

You may be tempted to use PMR446 (in Europe) or FRS, GMRS, MURS (in the USA) frequencies. Do note however that there are restrictions on these bands that make this transceiver illegal for use.

Table of Contents

Chapter1. Getting Started

1.1 Regulations and Safety Warnings
1.2 Content of the packaging
1.3 Main features
Chapter 2. Charging the Battery
2.1 Charging the Battery Pack
2.2 Charger Supplied
2.3 Use Caution with the Li-ion Battery
2.4 How to Charge
2.5 LED Indicator

Chapter3. Installation of Accessories

3.1 Installing / Removing the Antenna
3.2 Installing the belt clip
3.3 Installing the battery pack
3.4 Additional Speaker/Microphone (Optional)
Chapter4. Radio Overview
4.1 Buttons and controls of the radio
4.2 Display of the radio
4.3 Status Indications
4.4 Main keypad controls
Chapter5. Basic Operations
5.1 Power on the radio
5.2 Adiusting the volume

5.3 Making a call 5.4 Channel selection 5.5 Frequency (VFO) mode 5.6 Channel (MR) mode Chapter 6. Advanced Features 6.1 Frequency scanning 6.2 Channel scanning 6.3 Tone scanning 6.4 Dual Watch 6.5 Cursor \checkmark \land Conversion (A/B) 6.6 High/low power fast selection 6.7 Keypad lock 6.10 1000Hz, 1450Hz, 1750Hz Tone-burst 6.11 Manual Programming (Channels Memory) 6.12 Repeaters Programming 6.14 One touch frequency Search Chapter7. Working the MENU System 7.1 Basic use 7.2 Using short-cuts 7.3 Functions and operations Appendix A. - Technical Specifications Appendix B. - Trouble shooting guide Appendix C. - Shortcut Menu operations

Chapter1. Getting Started

1.1 Regulations and Safety Warnings

■EU Regulatory Conformance

As certified by the qualified laboratory, the product is in compliance with the essential requirements and other relevant provisions of the Directive 1999/5/EC (2014/53/EU). All applicable EU regulations are regarded (2006/66/EC, 2011/65/EU, 2012/19/EU). Please note that the above information is applicable to EU countries only.

■FCC Part15/IC Compliance

FCC Part 15 Compliance

This device complies with Part 15 of the FCC rules. Operation is subjected to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void your authority to operate the equipment.

Avis de conformité à la FCC : Ce dispositif a été testé et s'avère conforme à l'article 15 des règlements de la Commission fédérale des communications (FCC). Ce dispositif est soumis aux conditions suivantes: 1) Ce dispositif ne doit pas causer d'interférences nuisibles et; 2) Il doit pouvoir supporter les parasites qu'il reçoit, incluant les parasites pouvant nuire à son fonctionnement.

Tout changement ou modification non approuvé expressément par la partie responsable pourrait annuler le droit à l'utilisateur de faire fonctionner cet équipement.

IC Compliance

This device complies with Industry Canada license-exempt RSS standard(s).Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Changes or modifications not expressly approved by the party responsible for compliance could void your authority to operate the equipment.

Cet appareil est conforme aux normes RSS exemptes de licences d'Industrie Canada. Son fonctionnement est soumis aux

deux conditions suivantes : (1) cet appareil ne doit pas causer d'interférences nuisibles et (2), il doit pouvoir accepter les interférences, incluant celles pouvant nuire à son fonctionnement normal.

Tout changement ou modification non approuvé expressément par la partie responsable pourrait annuler le droit à l'utilisateur de faire fonctionner cet équipement.

FCC RF Exposure

WARNING! It is up to the user to properly operate this radio transmitter to insure safe operation. Please adhere to the following:

Do not use the radio with a damaged antenna. If a damaged antenna comes into contact with the skin, a minor burn may result.

Please contact your local dealer for a replacement antenna.

Hand-Held Operation (Held-to-Face)

This device was evaluated for typical hand-held (held-to-face) operations with a 1 inch spacing from the front of the radio. For hand-held operation, the radio should be held 1 inch from the user's face in order to comply with FCC RF exposure requirements.

Body-Worn Operation

This device was evaluated for body-worn operations with the supplied belt-clip accessory. (All necessary accessories are included in the package; any additional or optional accessories are not required for compliance with the guidelines.) Third party accessories (unless approved by the manufacturer) should be avoided as these might not comply with FCC RF exposure guidelines.

For body worn operation, this device has been tested and meets the Industry Canada RF exposure guidelines when used with our company accessories supplied or designated for this product. Use of other accessories may not ensure compliance with Industry Canada RF exposure guidelines.

Fonctionnement de l'appareil, lorsque porté sur le corps. Cet appareil a été testé et s'est avéré conforme aux normes d'Industrie Canada et approuvé pour le port sur le corps à l'aide des accessoires notre société inclus et conçus pour cet appareil. L'utilisation d'accessoires ne respectant pas les exigences d'exposition RF d'Industrie Canada doit être évitée.

Precautions for Portable Terminals

Operating Prohibitions

To protect you against any property loss, bodily injury or even death, be sure to observe the following safety instructions:

- 1. Do not operate the product in a location containing fuels, chemicals, explosive atmospheres and other flammable or explosive materials. In such location, only an approved Ex-protection model is allowed for use, but any attempt to assemble or disassemble it is strictly prohibited.
- 2. Do not operate the product near or in any blasting area.
- 3. Do not operate the product near any medical or electronic equipment that is vulnerable to RF signals.
- 4. Do not hold the product while driving.
- 5. Do not operate the product in any area where use of wireless communication equipment is completely prohibited.

Important Tips

To help you make better use of the product, be sure to observe the following instructions:

- 1. Do not use any unauthorized or damaged accessory.
- 2. Keep the product at least 2.5 centimeters away from your body during transmission.
- 3. Do not keep the product receiving at high volume for a long time.
- 4. For vehicles with an air bag, do not place the product in the area over the air bag or in the air bag deployment area.
- 5. Keep the product and its accessories out of reach of children and pets.
- 6. Please operate the product within the specified temperature range.
- Continuous transmission for a long time may lead to heat accumulation within the product. In this case, please keep it at a proper location for cooling.
- 8. Handle the product with care.
- 9. Do not disassemble, modify or repair the product and its accessories without authorization.

Precautions for Batteries

Charging Prohibitions

To protect you against any property loss, bodily injury or even death, be sure to observe the following safety instructions:

- 1. Do not charge or replace your battery in a location containing fuels, chemicals, explosive atmospheres and other flammable or explosive materials.
- 2. Do not charge your battery that is wet. Please dry it with a soft and clean cloth prior to charge.
- 3. Do not charge your battery suffering deformation, leakage and overheat.
- 4. Do not charge your battery with an unauthorized charger.
- 5. Do not charge your battery in a location where strong radiation is present.

6. Overcharge shall always be prohibited for it may shorten the life of your battery.

Maintenance Instructions

To help your battery work normally or prolong its life, be sure to observe the following instructions:

- 1. Accumulated dust on charging connector may affect normal charging. Please use a clean and dry cloth to wipe it on a regular basis.
- 2. It is recommended to charge the battery under 5°C~40°C. Violation of the said limit may cause battery life reduction or even battery leakage.
- 3. To charge a battery attached to the product, turn it off to ensure a full charge.
- 4. Do not remove the battery or unplug the power cord during charging to ensure a smooth charging process.
- 5. Do not dispose of the battery in fire.
- 6. Do not expose the battery to direct sunlight for a long time nor place it close to other heating sources.
- 7. Do not squeeze and penetrate the battery, nor remove its housing.

Transportation Instructions

- 1. Damaged batteries must not be transported.
- 2. To avoid short circuit, separate the battery from metal pars or from each other if two or more batteries are transported in one packaging.
- 3. The radio must be switched off and secured against switch-on, if the battery is attached.

The content of the shipment must be declared in the shipping documents and by a Battery Shipping Label on the packaging. Contact your hauler for the local regulations and further information.

Maintenance

Your Two Way Radio is an electronic product of exact design and should be treated with care.

The suggestions below will help you to fulfill any warranty obligations and to enjoy this product for many years.

- Do not attempt to open the radio for any reason! The radio's precision mechanics and electronics require experience and specialized equipment; for the same reason, the radio should under no circumstances be realigned as it has already been calibrated for maximum performance. Unauthorized opening of the transceiver will void the warranty.
- Do not store the Radio under the sunshine or in hot areas.
- High temperatures can shorten the life of electronic devices, and warp or melt certain plastics.
- Do not store the radio in dusty and dirty areas.

- Keep the Radio dry. Rainwater or damp will corrode electronic circuits.
- If it appears that the Radio diffuses peculiar smell or smoke, please shut off its power immediately and take off the charger or battery from the radio.
- Do not transmit without antenna.

1.2 Content of the packaging

- 1 Radio
- 1 Fast desktop charger
- 1 Antenna

If any item is missing, please verify with your dealer.

1.3 Main features

- Frequency band: VHF/UHF (Frequency limited)
- Up to 128 memory channels
- 50 CTCSS tones and 210 DCS codes
- SOS Emergency function
- FM radio receiver (87.5-108MHz)
- Channel or frequency mode selection
- TOT (Time out timer)
- Reverse function
- CTCSS and DCS codes research
- Busy Channel Lockout function (BCL)
- Frequency step: 2.5/5/6.25/10/12.5/25KHz
- Repeater shift
- · VOICE: vocal indication of the function selected
- Li-lon battery pack

- 1 Li-lon battery pack
- Wall adaptor
- 1 Belt clip
- VHF and UHF bands and channel name displayed
- Squelch adjustable in 9 levels
- 1750Hz tone for repeaters
- LCD display with backlight adjustable in 3 colors
- VOX, Scan, Dual Watch functions
- Power Save
- DTMF function
- Alarm function
- · Setting and storing of channel names
- High/low power selection
- Frequency offset (adjustable): 0-69.990MHz
- 2pin Kenwood accessory jack
- Keypad lock
- · Battery allows direct charging from the DC port

Chapter2. Battery Information

2.1 Charging the Battery Pack

The Li-ion battery pack is not charged at the factory; please charge it before use. Charging the battery pack for the first time after purchase or extended storage (more than 2 months) may not bring the battery pack to its normal maximum operating capacity. Best operation will require fully charging/ discharging the battery two or three times before the operating capacity will reach its best performance. The battery pack life may be depleted when it's operating time decreases even though it has been fully and correctly charged. If this is the case, replace the battery pack.

2.2 Charger Supplied

Please use the specified charger provided by BAOFENG. Other models may cause explosion and personal injury. After installing the battery pack, and if the radio displays low battery with a voice prompt, please charge the battery.

2.3 Use Caution with the Li-ion Battery

- a. Do not short the battery terminals or throw the battery into a fire. Never attempt to remove the casing from the battery pack, as BAOFENG cannot be held responsible for any accident caused by modifying the battery.
- b. The ambient temperature should be between 5°C-40°C (40°F 105°F) while charging the battery. Charging outside this range may not fully charge the battery.
- c. Please turn off the radio before inserting it into the charger. It may otherwise interfere with correct charging.
- d. To avoid interfering with the charging cycle, please do not cut off the power or remove the battery during charging until the green light is on.
- e. Do not recharge the battery pack if it is fully charged. This may shorten the life of the battery pack or damage the battery pack.
- f. Do not charge the battery or the radio if it is damp. Dry it before charging to avoid damage.

WARNING !

When keys, ornamental chain or other electric metals contact the battery terminal, the battery may become damage or injure a human. If the battery terminals are short circuited it will generate a lot of heat. Take care when carrying and using the battery. Remember to put the battery or radio into an insulated container. Do not put it into a metal container.

2.4 How to Charge

- a. Plug the AC adaptor into the AC outlet, and then plug the cable of the AC adaptor into the DC jack located on the back of the charger. The indicator light blinks orange and is then ready to charge a battery.
- b. Plug the battery or the radio into the charger. Make sure the battery terminals are good in contact with charging terminals. The indicator light turns to red--- charging begins.
- c. It takes approximately 2-5 hours to fully charge the battery. When the lamp lights green, the charging is completed. Remove the battery or the radio unit with its battery from socket.

When charging a radio (with battery) the indicating lamp will not turn into green to show the fully charged status if the radio is powered on. Only when the radio is switched off will the lamp indicate normal operation. The radio consumes energy when it is power-on, and the charger cannot detect the correct battery voltage when the battery has been fully charged. So the charger will charge the battery in constant voltage mode and fail to indicate correctly when the battery has been fully charged.

2.5 LED Indicator

STATUS	LED
No Battery	Green and red alternately flashing
Charge Normally	Red
Fully Charged	Green
Trouble	Red blinks fast for a long time

NOTE: Trouble means battery too warm, battery short-circ



Chapter3. Installation of Accessories

Before the radio is ready for use we need to attach the antenna and battery pack, as well as charge the battery.

3.1 Installing/ Removing the Antenna

- a. Installing the Antenna: Screw the antenna into the connector on the top of the transceiver by holding the antenna at its base and turning it clockwise until secure.
- b. Removing the Antenna: Turn the antenna counter-clockwise to remove it.

3.2 Installing the belt clip

- a. At the back of the radio there are two parallel screws mounted above the battery, remove these and thread them through the holes on the belt clip as you screw them back into the radio body.
- b. Removing the Belt Clip: Unscrew counter-clockwise to remove the belt clip.

3.3 Installing the battery pack

Before attaching or removing the battery make sure your radio is turned off by turning the power/volume knob all the way counter-clockwise.

- a. Make sure the battery is aligned in parallel with the radio body with the lower edge of the battery about 1-2cm below the edge of the radio.
- b. Once aligned with the guide-rails, slide the battery upward until you hear a click as the battery locks in place.





Remove the battery pack

To remove the battery, press the battery release above the battery pack, as you slide the battery downward.

3.4 Installing the Additional Speaker/Microphone (Optional)

Pry open the rubber MIC-Headset jack cover and then insert the Speaker / Microphone plug into the double jack.



Chapter4. Radio Overview

4.1 Buttons and controls of the radio



1. Antenna	7. PTT - Push to talk	13. BAND key
2. LED flashlight	8. VFO/MR mode key	14. Keypad
3. Power / Volume knob	9. Status LED	15. Speaker and microphone
4. Two-line LCD	10. Lanyard loop	16. Battery pack
5. Call key	11. Accessory jack	17. Battery contacts
6. Monitor key	12. A / B select key	18. Battery release latch

4.2 Main controls and parts of the radio

LCD Display

Tull LDS VOX +-	RNASS™I
	75 88 25 × *
ST2T DTMF	75 88 25 * *

lcon	Description	lcon	Description
:88	Memory channel	R	Reverse function enabled
75 25	Least significant modifiers.	N	Narrowband enabled
СТ	CTCSS enabled	Ē	Battery level indicator
DCS	DCS enabled	8	Keypad lock enabled
+-	Frequency shift direction if enabled in VFO		Transmit power level indicator According to Power (High, Low)
s	Dual watch enabled		Indicates active band or channel
vox	VOX enabled	T.III	Squelch Open/ Close Indicator

Note: Even though it is a seven character by two-line display, channel memories are only configurable to six character names.

Battery Level Indicator

When the battery level indicator reads 💭 the battery is depleted. At this point the radio will start beeping periodically as well as flash the backlight of the display and when voice prompts are enabled, a "Low Voltage" announcement will be heard,

indicating that you need to change your battery or put your radio in the charger.

4.3 Status Indications

The status LED has a very simple and traditional design. When you receive a signal it turns green, when you transmit it turns red, and it's off in standby.

LED Indicator	Radio Status
Constant Red	Transmitting.
Constant Green	Receiving.

4.4 Main keypad controls

- [CALL] key: Press it for a short time to turn on the FM radio. Press it again to turn it off. If you press it for a long time you will activate the alarm function. Press it again to turn off this feature.
- [MON] key: Press it for a short time to light up the flashlight. If you push this button again, the flashlight will light up to strobe mode. Press MONI a third time to turn off the flashlight.

To activate the Monitor function presses the button for a long time.

• [VFO/MR] key: Press it for switches between Frequency (VFO) Mode and Memory (MR) mode. Memory mode is sometimes also referred to as Channel mode.

To save frequencies to channel memory you must be in Frequency (VFO) mode.

- [A/B] key: Press it for switches between A (upper) and B (lower) displays. The frequency or channel on the selected display becomes the active listening and transmit frequency or channel. To save frequencies to channel memory you must be on the A display. When listening to broadcast FM, the [A/B] key switches between 65-75 MHz and 76-108 MHz band
- [MENU] key: it is used for activating the MENU, choose each MENU selection and confirm the parameter.
- [A] key: Press it for more than 2 seconds, the channel and frequency will move upwards rapidly; in SCAN mode, press this control to move the scanning upwards.
- [V] key: Keep it pressed it for more than 2 seconds, the channel and frequency will move downwards rapidly; in SCAN mode, press this control to move the scanning downwards.
- [EXIT] key: push this button to exit the functions and settings.
- [BAND] key: Press it for switch between VHF or UHF bands. Press and hold the [BAND] key to activate the one-touch

search function. When listening to broadcast FM, the [BAND] key switches between 65-75 MHz and 76-108 MHz bands.

Numeric keypad

With these keys you can input the information or your selections on the radio. In tx mode, push the number keys to send a corresponding DTMF code.

• *SCAN Key

A short momentary press of the key enables the reverse function.

When listening to broadcast FM a momentary press will start the scanning. Scanning in broadcast FM will stop as soon as an active station is found, regardless of scanner resume method.

To enable the scanner, press and hold the [*SCAN] key for about two seconds.

Zero 0 Key

The BAOFENG UV-5R features a battery voltage meter that the current voltage of the battery on the display. To see the voltage displayed, press and hold the **[0SQL]** key for about two seconds.

• #**пО** key

If you press shortly [#0] you will switch to High or Low output power. If you press this button for more than 2 seconds you will lock/unlock the keypad.

Chapter5. Basic Operations

5.1 Power on the radio

To turn the unit on, simply rotate the **Volume/Power** knob clockwise until you hear a "click". If your radio powers on correctly there should be an audible double beep after about one second and the display will show a message or flash the LCD depending on settings for about one second. Then it will display a frequency or channel. If the Voice prompt is enabled, the voice will announce "frequency mode" or "channel mode".

Turn the Volume/Power knob counter-clock wise all the way until you hear a "click". The unit is now off.

5.2 Adjusting the volume



To turn up the volume, turn the **Volume/Power** knob clock-wise. To turn the volume down, turn the **Volume/Power** knob counter-clock-wise. Be careful not to turn it too far, as you may inadvertently turn your radio off.

5.3 Making a call

NOTE: Press the [A/B] key to switch the main channel to the other channel if there is 2 channels shown on the display. Press the [VFO/MR] key to switch between VFO and channel display.

- Channel mode call: After selecting a channel, hold down the **[PTT]** key to initiate a call to the current channel. Speak into the microphone with normal tone. Initiate a call, the red LED is on.
- Frequency mode call: Press the [VFO/MR] key to switch to the frequency mode, the frequency range allowed entering, press the [PTT] key, a call to the current channel. Speak into the microphone with normal tone. Initiate a call, the red LED is on.
- Receive a call: When you release the **[PTT]** key, you can answer it without any action.

When receiving a call, the green LED is on.

NOTE: To ensure the best reception volume, keep the distance between the microphone and the mouth at the time of transmission from 2.5 cm to 5 cm.

5.4 Channel selection

There are two modes of operation: Frequency (VFO) mode, and Channel or Memory (MR) mode. For everyday use, Channel (MR) mode is going to be a whole lot more practical than Frequency (VFO) mode. However, Frequency (VFO) mode is very handy for experimentation out in the field. Frequency (VFO) mode is also used for programming channels into memory.

In Channel (MR) mode you can navigate up and down the channel by using the \blacktriangle and \triangledown keys. Ultimately which mode you end up using will depend entirely on your use case.

5.5 Frequency (VFO) mode

In Frequency (VFO) mode you can navigate up and down the band by using the ▲ and ▼ keys. Each press will increment or decrement your frequency according to the frequency step you've set your transceiver to.

You can also input frequencies directly on your numeric keypad with kilohertz accuracy.

The following example assumes the use of a 12.5 kHz frequency step.

Example. Entering the frequency 432.6125 MHz on display A

a. Use the [VFO/MR] key to switch to Frequency (VFO) mode.
b. Press [A/B] until the ▲ icon appears next to the upper display.
c. Enter [4][3][2][6][1][2][5] on the numeric keypad.

WARNING!



Just because you can program in a channel does not mean you're automatically authorized to use that frequency. You may be tempted to use PMR446, FRS, GMRS and MURS (in USA) frequencies. Do note however that there are restrictions on these bands that make this transceiver illegal for use. Contact your local regulatory body for further information on what laws, rules and regulations apply to your area.

5.6 Channel (MR) mode

The use of Channel (MR) mode is dependent on actually having programmed in some channels to use. Once you have channels programmed and ready, you can use the ▲ and ▼ keys to navigate between channels. Note: If you have channels programmed with Transmit power set to Low, you can use the [#m0] key to momentarily switch over to mid or high power if you're having trouble getting through.

Chapter6. Advanced Features

6.1 Frequency scanning

This function can scan the frequency.

- a. In frequency mode, press [*/scan] key for more than 2 seconds. The radio will start scanning the frequency according to the set frequency step.
- **b.** You can change the scanning direction with the \blacktriangle and \blacktriangledown keys.
- c. Press any key to stop the scanning.

Note: for Scan mode, see Menu No.18.

6.2 Channel scanning

This function can scan the channels.

a. In channels mode, press [*scan] key for more than 2 seconds. The radio will start scanning according to the channel you

set.

b. You can change the scanning direction with the \blacktriangle and \blacktriangledown keys.

c. Press any key to stop scanning.

Note: for Scan mode, see Menu No.18.

6.3 Tone Scanning

Scanning for CTCSS and DCS Tones/Codes

Scanning for a CTCSS tone or DCS code can be done while Frequency Mode (VFO) or Channel Mode (MR) is selected. Only when VFO mode is selected, can the detected tone/code be saved to menu 11/10.

CTCSS tone and DCS code scanning mode can be accessed with or without a signal being present. The scanning process itself only occurs while a signal is being received.

Not all repeaters requiring a CTCSS tone or DCS code for access will transmit one back. In that case, the transmitter of a station that can access the repeater would need to be scanned. In other words: this would be done by listening to stations on the repeater's input frequency.

Scanning for CTCSS Tone

1. Press the [MENU] [1] [1] to come to Menu 11: R-CTCS

2. Press the [MENU] key to select. Insure you have a tone activated (and it is not off)

3. Press the [*SCAN] to begin CTCSS scanning

A flashing "CT" will be in the left status display to indicate the radio is in CTCSS scanning mode. In this mode, whenever the radio is receiving an RF signal on the selected MR channel or VFO frequency, the lower display will cycle through the CTCSS tones as they are being tested. Once the frequency of the received CTCSS tone is determined, the "CT" indicator will stop flashing.

Press the **[MENU]** key to save the scanned tone into memory (VFO Mode Only) then press the **[EXIT]** key to exit the menu. *Don't forget to set VFO menu 11 back to OFF when the CTCSS tone is no longer required.*

Scanning for a DCS tone

- 1. Press the [MENU] [1] [0] to come to Menu 10: R-DCS
- 2. Press the [MENU] key to select. Insure you have a tone activated (and it is not off)

3. Press the [*SCAN] to begin DCS scanning

A flashing "DCS" will be in the left status display to indicate the radio is in DCS scanning mode. In this mode, whenever the radio is receiving an RF signal on the selected MR channel or VFO frequency, the lower display will cycle through the DCS codes as they are being tested. Once the bits of the received DCS code are determined, the "DCS" indicator will stop flashing.

Press the **[MENU]** key to save the scanned tone into memory (VFO Mode Only) then press the **[EXIT]** key to exit the menu. *Don't forget to set VFO menu 10 back to OFF when the DCS tone is no longer required.*

6.4 Dual Watch

The BAOFENG UV-5R features Dual Watch functionality (single receiver) with the ability to lock the transmit frequency to one of the two channels it monitors.

· Enabling or disabling Dual Watch mode

- 1. Press the [MENU] [7] to get to MENU 7: TDR.
- 2. Press [MENU] key to select.
- 3. Use the \blacktriangle and \blacktriangledown keys to enable or disable.
- 4. Press the [MENU] key to confirm.
- 5. Press the [EXIT] key to exit the menu.

Due to the way the BAOFENG UV-SR is constructed, whenever one of the A or B Frequencies (VFO/MR) goes active, it will default to transmit on that channel. This behavior can be inconvenient, especially if when monitoring a frequency, you should not transmit on. There is a menu option available to lock the transmitter to one of the A or B channels.

· Locking the Dual Watch transmit channel

- 1. Press the [MENU] [3][4] to get to MENU 34: TDR-AB.
- 2. Press [MENU] key to select.
- 3. Use the \blacktriangle and \blacktriangledown keys to select A (upper) or B (lower) display.
- 4. Press the [MENU] key to confirm.
- 5. Press the [EXIT] key to exit the menu.

If you want to momentarily override the lock without having to setting the menu option to OFF, you can do so by pressing the [A/B] key an instant before pressing the PTT.

Another option is to disable menu [7] (TDR) to override the lock. Then re-enable TDR when you want the lock resumed

6.5 Cursor ▼ ▲ Conversion (A/B)

Directly press [A/B] key to move the cursor up and down. Then, you can modify or confirm the parameters indicated by the cursor.

Important1: UV-5R has a dual-frequency display function. In frequency mode, you will see on the display two different receiving and transmitting frequencies; while in channel mode the two different channels will be displayed.

▼ is displayed next to the channel.

6.6 High/low power fast selection

In channel mode, press [#TTO] key to shift between high and low power.

6.7 Keypad lock

This function locks the keypad to prevent accidental pressure of the controls. To unlock the keypad, press **[#TTO**] for more than 2 seconds.

6.8 FM Radio (FM)

The frequency range to listen to the radio is 65-108MHz. When listening to broadcast FM, press **[A / B]** key switches between 65-75 MHz and 76-108 MHz band.

- a. In frequency or channel mode, Press [CALL] to turn on the radio.
- b. Select the desired radio frequency with the \blacktriangle or \blacktriangledown keys or input the frequency. or
 - Press [* SCAN] to automatically search a radio station.

c. Press [CALL] to exit FM radio.

Note: while you are listening to the radio, the frequency or channel of A / B receiving signal will

automatically switch to the frequency or channel mode for normal transmitting and receiving. When the signal disappears the radio will automatically switch again to FM radio mode.

6.9 Flashlight

This function is very useful for night illumination.

To turn it on press MON; push it again, the flash light will be strobe; push it again: it will turn off.

6.10 1000Hz, 1450Hz, 1750Hz Tone-burst

To send out a tone-burst; you simultaneously will press a key while holding down the PTT. No further configuration required using this feature.

The following configurations will transmit accordingly:

- [PTT] + [CALL] = Transmits 1000Hz Tone Burst
- [PTT] + [VFO/MR] = Transmits 1450Hz Tone Burst
- [PTT] + [A/B] = Transmits 1750Hz Tone Burst

If you have the keypad lock enabled on your radio, you can still send a 1750Hz tone the regular way without having to unlock your radio.

6.11 Manual Programming (Channels Memory)

Memory channels are an easy way to store commonly used frequencies so that they can easily be retrieved at a later date. The BAOFENG UV-5R features 128 memory channels that each can hold: Receive and transmit frequencies, transmit power, group signaling information, bandwidth, ANI/ PTT-ID settings and a six character alphanumeric identifier or channel name¹.

Frequency Mode vs. Channel Mode

Switch between Modes by Using the **[VFO/MR]** Front Panel Button. These two modes have different functions and are often confused.

Frequency Mode (VFO) : Used for a temporary frequency assignment, such as a test frequency or quick field programming if permitted.

Channel Mode (MR) : Used for selecting preprogrammed channels.

Ex 1. Programming a Channel Repeater Offset with CTCSS Tone

EXAMPLE New memory in Channel 10: RX = 432.000 MHz TX = 437.000 MHz (This is a (+ 5) Offset) TX CTCSS tone 123.0 a. Change from Menu to Menu by pressing the [EXIT] b. Set radio to VFO Mode by pressing [VFO/MR] Channel number at the right will disappear. c. [MENU] [2][8] [MENU] [1][0] [MENU] [EXIT] d. [MENU] [1][3] [MENU] 123.0 [MENU] [EXIT] e. Enter RX frequency (Ex. 432000) f. [MENU] [2][7] [MENU] [1][0] [MENU] SERUTI	key. Deletes Prior Data in channel (Ex. 10) Selects desired TX encode tone Enter the desired channel (Ex 10) BY has been added
>>[EAT] g. Enter TX frequency (Ex. 437000) h. [MENU] [2][7] [MENU] [1][0] [MENU]	Enter the same channel (Ex 10)
>> [EXIT] i. [VFO/MR] Return to MR Mode. Channel number w	TX has been added ill re-appear.
Ex 2. Programming a Simplex Channel with CTCSS tor EXAMPLE New memory in Channel 10: RX = 436.000 MHz TX CTCSS tone 123.0	ne
 a. Change from Menu to Menu by pressing the [EXIT] b. Set radio to VFO Mode by pressing [VFO/MR] Changel number at the right will disappear 	button.
c. [MENU] [2][8] [MENU] [1] [0] [MENU] [EXIT] d. [MENU] [1][3] [MENU] 123.0 [MENU] [EXIT]	Deletes Prior Data in channel (Ex. 10) Select desired TX encode tone (Ex 123 CTCSS)
e. Enter RX frequency (Ex. 436000) f. [MENU] [2][7] [MENU] [1][0] [MENU]	Enter the desired channel (Ex 10)
>> [EXIT] g. [VFO/MR] Return to MR Mode. Channel number w	Channel has been added ill re-appear.

6.12 Repeaters Programming

The following instructions assume that you know what transmit and receive frequencies your repeater employs, and that you're authorized to use it.

- a. Set the radio to Frequency (VFO) mode with the [VFO/MR] key.
- b. Enter the repeater's output (your receiving) frequency by either using the ▲ and ▼ keys, or by entering it directly on the numerical keypad.
- c. Press the [MENU] key to enter the menu.
- d. Enter [2][6] on the numeric keypad to get to frequency offset.
- e. Press [MENU] key to select.
- f. Use the numerical keypad to enter the specified frequency offset. See the section called "26 OFFSET Frequency shift amount" for details.
- g. Press [MENU] to confirm and save.
- h. Enter [2][5] on the numeric keypad to get to offset direction.
- i. Use the \blacktriangle/∇ keys to select + (positive) or (negative) offset.
- j. Press [MENU] to confirm and save.
- k. Optional:
- a). Save to memory, see the section called "Manual programming" for details.
- b). Set up CTCSS; see the section called "CTCSS" for details.

I. Press [EXIT] to exit the menu. If everything went well, you should be able to make a test call through the repeater.

NOTE:

If you're experiencing problems making a connection to the repeater, check your settings and/or go through the procedure again. Certain Amateur Radio repeaters (especially in Europe) use a 1750Hz tone burst to open up the repeater. To see how this is done with the BAOFENG UV-5R, see the section called "1750Hz Tone-burst".

If you're still unable to make a connection, contact the person in charge of the radio system with your employer or your local amateur radio club, as the case may be.

If you for some reason want to listen to the repeater's input frequency instead, press [*/SCAN] key momentarily and you'll reverse your transmit and receive frequencies.

This is indicated in the LCD on the radio with an R in the top row, next to the + and - for the offset direction.

6.13 DTMF

DTMF is an in-band signaling method using dual sinusoidal signals for any given code. Originally developed for telephony systems, it has proved a very versatile tool in many other areas.

In two-way radio systems, DTMF is most commonly used for automation systems and remote control. A common example would be in amateur radio repeaters where some repeaters are activated by sending out a DTMF sequence (usually a simple single-digit sequence).

	1209 Hz	1336 Hz	1477 Hz	1633 Hz
697 Hz	1	2	3	А
770 Hz	4	5	6	В
852 Hz	7	8	9	С
941 Hz	*	0	#	D

The BAOFENG UV-5R EU has a full implementation of DTMF, including the A, B, C and D codes. The numerical keys, as well as the **[*SCAN]**, and **[#mO]**, keys correspond to the matching DTMF codes as you would expect. The A, B, C and D codes are located in the [MENU], $[\blacktriangle], [\checkmark]$ and **[EXIT]** keys respectively (†).

To send DTMF codes, press the key(s) corresponding to the message you want to send while holding down the PTT key. *If you have the keypad lock enabled on your radio, you can still send DTMF tones the regular way without having to unlock your radio.*

6.14 One touch frequency Search

(1) The radio will act as a receiver. Press and hold the [BAND] key, and the screen will display "SEARCH UHF".

(2) If the transmitter continues to transmit and the unit receives an effective frequency (the strongest and stable signal), the received frequency will be displayed. If there is a CTCSS or DCS,

the CTCSS or DCS value is displayed, and if there is no CTCSS or DCS, NONE is displayed

(3) You can press the [MENU] key to save the Search frequency and CTCSS or DCS to the channel. Note: During frequency Search, press the [#TTO] key on the radio to switch between UHF or VHF bands.

Chapter7. Working the MENU System

For a complete reference on available menu items and parameters, see Appendix C, Shortcut Menu operations. Note: in channel mode, the setting of these features is not possible: CTCSS/ DCS tones, wide/narrow bandwidth, PTT-ID, Busy channel lock out, channel name edit.

7.1 Basic use

Using the menu with arrow keys

- a. Press the [MENU] key to enter the menu.
- **b.** Use the [▲] and [▼] keys to navigate between menu items.
- c. Once you find the desired menu item, press [MENU] again to select that menu item.
- **d.** Use the $[\blacktriangle]$ and $[\blacktriangledown]$ keys to select the desired parameter.
- e. When you've selected the parameter you want to set for a given menu item;
 - a). To confirm your selection, press [MENU] and it will save your setting and bring you back to the main menu.
 - b). To cancel your changes, press [EXIT] and it will reset that menu item and bring you out of the menu entirely.
- f. To exit out of the menu at any time, press the [EXIT] key.



7.2 Using short-cuts

As you may have noticed if you looked at **Appendix C, Shortcut Menu operations**, every menu item has a numerical value associated with it. These numbers can be used for direct access of any given menu item.

The parameters also have a number associated with them, see **Appendix C, Shortcut Menu operations** for details. Using the menu with short-cuts

- a. Press the [MENU] key to enter the menu.
- **b.** Use the numerical keypad to enter the number of the menu item.
- c. To enter the menu item, press the [MENU] key.
- d. For entering the desired parameter you have two options:
 - a). Use the arrow keys as we did in the previous section; or
 - **b**). Use the numerical keypad to enter the numerical short-cut code.
- e. And just as in the previous section;
 - a). To confirm your selection, press [MENU] and it will save your setting and bring you back to the main menu.
 - b). To cancel your changes, press [EXIT] and it will reset that menu item and bring you out of the menu entirely.
- f. To exit out of the menu at any time, press the [EXIT] key.
- g. All further examples and procedures in this manual will use the numerical menu short- cuts.

Appendix A. – Trouble shooting guide

Phenomena	Analysis	Solution
	The battery may be installed improperly.	Remove and reattach the battery.
You cannot turn on the radio	The battery power may run out.	Recharge or replace the battery.
fou cannot turn on the radio.	The battery may suffer from poor contact caused by dirty or damaged	Clean the battery contacts or replace the battery.
	battery contacts.	
	The battery voltage maybe low.	Recharge or replace the battery.
During receiving the voice is	The volume level may be low.	Increase the volume.
work or intermittent	The antenna maybe loose or maybe installed incorrectly.	Turnoff the radio, and then remove and reattach
weak of intermittent.		the antenna.
	The speaker maybe blocked.	Clean the surface of the speaker.
You cannot communicate with	The frequency or signaling type maybe inconsistent with that of other	Verify that your TX/RX frequency and signaling
other group members	members.	type are correct.
other group members.	You may be too far away from other members.	Move towards other members.
You hoor unknown voices or	You may be interrupted by radios using the same frequency.	Change the frequency, or adjust the squelch level.
rou near unknown voices or	The radio in analog mode maybe set with no signaling.	Request your dealer to set signaling for the
noise:		current channel to avoid interference
	You may be too far away from other members.	Move towards other members.
You are unable to hear anyone	You may be in an unfavorable position. For example, your	Move to an open and flat area, restart the radio,
because of too much noise	communication may be blocked by high buildings or blocked in an	and try again.
	underground area.	
and mas.	It may be the result of external disturbance (such as electromagnetic	Stay away from equipment that may cause
	interference).	interference.
The radio keeps transmitting	VOX may be turned on or the headset is not installed in place	Turn off the VOX function. Check that the
The radio keeps transmitting.		headphones are in place.

NOTE: If the above solutions cannot fix your problems, or you may have some other queries, please contact your dealer for more technical support.

Appendix B. - Technical Specifications

Frequency band	FM65-108MHz; AM108-136MHz(Rx); 136-174MHz (Rx);
	220-260MHz (Rx); 400-520MHz (Rx);350-390MHz (Rx)
	144-148MHz (Tx); 420-450MHz(Tx)
Memory channels	128
Power supply	batteria Li-Ion da 7.4V/1800 mAh (BL-5)
Operating temperature	-10°C to + 45°C
Working mode	monoband/dualband
Modulation	F3E(FM)
Max. frequency deviation	≤ ±5KHz
Spurious radiation	< -60dB
Frequency stability	±2.5 ppm
Rx sensitivity	< 0.2uV
Audio output power	≥ 500mW
Dimensions	58x109x33mm (LxAxP)
Weight	208g

Specifications are subject to change without notice.

WARNING. Direct plug-in ac/dc power supply must be used for disconnecting the transceiver from the mains; the desktop charger must be positioned close to the unit and easily accessible.

Appendix C. - Shortcut Menu operations

MEN U No.	Name (Full Name)	Enter item	Select able
0	SQL - Squelch Level	MENU+0	0-9 Levels 0:Lowest 9:Highest
1	STEP –Step Frequency	MENU+1	2.5K/5.0K/6.25K/10.0K 12.5K/20.0K/25.0K/50.0K
2	TXP – Transmit Power	MENU+2	HIGH:5W(VHF) 4W(UHF)* Low:2W
3	SAVE - Battery Saving	MENU+3	OFF: 1:1 2:2 3:3 4:4
4	VOX - VOX	MENU+4	OFF, 1-9 OFF: off 1: Highest Sensitivity 9: Highest Sensitivity
5	WN-Wide/Narrow	MENU+5	WIDE:25.0K NARR:12.5K
6	ABR –Auto Backlight	MENU+6	OFF/1,2,38, 9,10 *Time-out for the LCD backlight. (seconds)
7	TDR – Dual Watch Operation	MENU+7	OFF ON *Monitor [A] and [B] at the same time. The display with the most recent activity ([A] or [B]) becomes the selected display.
8	BEEP - Keypad Beep	MENU+8	OFF ON *Allows audible confirmation of a key press.

9	TOT- Time-Out-Timer	MENU+9	15,30600S *This feature provides a safety switch that limits transmission time to a programmed value. This will promote battery conservation by not allowing you to make excessively long transmissions, and in the event of a stuck PTT switch it can prevent interference to other users as well as battery depletion
10	R-DCS - Receiver DCS	MENU+10	OFF D023ND754N D023ID754I *Mutes the speaker of the transceiver in the absence of a specific low-level digital signal. If the station you are listening to does not transmit this specific signal, you will not hear anything.
11	R-CTCS - Receiver CTCSS	MENU+11	OFF 67.0HZ254.1HZ *Mutes the speaker of the transceiver in the absence of a specific and continuous sub-audible signal. If the station you are Listening to does not transmit this specific and continuous signal, you will not hear anything.
12	T-DCS -Transmitter DCS	MENU+12	OFF D023ND754N D023ID754I *Transmits a specific low-level digital signal to unlock the squelch of a distant receiver (usually a repeater).

13	T-CTCS - Transmitter CTCSS	MENU+13	OFF 67.0HZ254.1HZ *Transmits a specific and continuous sub audible signal to unlock the squelch of a distant receiver (usually a repeater).
14	VOICE - Voice Reminding	MENU+14	OFF CHI ENG *Allows audible voice confirmation of a key press.
15	ANI-ID -ANI-ID	MENU+15	It can be programmed by software
16	DTMFST - DTMFST	MENU+16	OFF: No DTMF Side Tones are heard DT-ST : Side Tones are heard only from manually keyed DTMF codes ANI-ST: Side Tones are heard only from automatically keyed DTMF codes DT+ANI : All DTMF Side Tones are heard
17	S-CODE - Signal Code	MENU+17	1,,15
18	SC-REV - Scanner Resume Method	MENU+18	TO : Time Operation - scanning will resume after a fixed time has passed CO : Carrier Operation -scanning will resume after the signal disappears SE : Search Operation -scanning will not resume
19	PTT-ID - PTT-ID	MENU+19	OFF: No ID is sent BOT: The selected S-CODE is sent at the beginning EOT: The selected S-CODE is sent at the ending BOTH: The selected S-CODE is sent at the beginning and ending

20	PTT-LT – PTT ID delay	MENU+20	0,1,2,50ms *PTT-ID Delay (milliseconds)
21	MDF-A - Channel A Display Mode	MENU+21	FREQ: Displays programmed Frequency CH: Displays the channel number NAME: Displays the channel name *Note: Names must be entered using software.
22	MDF-B - Channel B Display Mode	MENU+22	FREQ: Displays programmed Frequency CH: Displays the channel number NAME: Displays the channel name *Note: Names must be entered using software.
23	BCL – Busy Channel Lock-out	MENU+23	OFF ON *Disables the [PTT] button on a channel that is already in use. The transceiver will sound a beep tone and will not transmit if the [PTT] button is pressed when a channel is already in use.
24	AUTOLK –Automatic Keypad Lock	MENU+24	OFF ON *When ON, the keypad will be locked if not used in 8 seconds. Pressing the [#m0] key for 2 seconds will unlock the keypad.
25	SFT-D – Frequency Offset Direction	MENU+25	OFF: TX = RX (simplex) +: TX will be shifted higher in frequency than RX - : TX will be shifted lower in frequency than RX
26	OFFSET -Frequency shift amount	MENU+26	00.00069.990 *Specifies the difference between the TX and RX frequencies

27	MEM-CH - Store a Memory Channel	MENU+27	000127 *This menu is used to either create new or modify existing channels (0 through 127) so that they can be accessed from MR/Channel Mode
28	DEL-CH - Delete a memory channel	MENU+28	000127 *This menu is used to delete the programmed information from the specified channel (0 through 127) so that it can either be programmed again or be left empty.
29	WT-LED- Standby Backlight	MENU+29	OFF/ BLUE/ ORANGE/ PURPLE
30	RX-LED- Receive Backlight	MENU+30	OFF/ BLUE/ ORANGE/ PURPLE
31	TX-LED- Transmit Backlight	MENU+31	OFF/ BLUE/ ORANGE/ PURPLE
32	AL-MOD - Alarm Mode	MENU+32	SITE: Sounds alarm through your radio speaker only TONE: Sending alarm tone CODE: Sending alarm code
34	TDR-AB - Transmit selection while in Dual Watch mode	MENU+34	OFF A band transmit (Upper row frequency) B band transmit (Bottom row frequency) *When enabled, priority is returned to selected display once the signal in the other display disappears.
35	STE - Squelch Tail Elimination	MENU+35	ON OFF *This function is used eliminate squelch tail noise between BAOFENG handhelds that are communicating directly (no repeater). Reception

			of a 55 Hz or 134.4 Hz tone burst mutes the audio long enough to prevent hearing any squelch tail noise.
36	RP-STE-Squelch Tail Elimination	MENU+36	OFF/ 1,2,310 *This function is used eliminate squelch tail noise when communicating through a repeater.
37	RPT-RL - Delay the squelch tail of repeater	MENU+37	OFF/ 1,2,310 *Delay the Tail Tone of Repeater (X100 milliseconds)
38	PONMSG-Power On Message	MENU+38	FULL: Performs an LCD screen test at power-on MSG: Displays a 2-line power on message *Controls the behavior of the display when the transceiver is turned on.
39	ROGER - Roger Beep	MENU+39	OFF ON *Sends an end-of-transmission tone to indicate to other stations that the transmission has ended.
40	RESET – Restore defaults	MENU+40	VFO: Menu initialization ALL: Menu and channel initialization *Resets the radio to factory defaults, with some exceptions.

Appendix D. - DCS Table

DCS CODE LIST

Number	Code								
1	D023N	2	D025N	3	D026N	4	D031N	5	D032N
6	D036N	7	D043N	8	D047N	9	D051N	10	D053N
11	D054N	12	D065N	13	D071N	14	D072N	15	D073N
16	D074N	17	D114N	18	D115N	19	D116N	20	D122N
21	D125N	22	D131N	23	D132N	24	D134N	25	D143N
26	D145N	27	D152N	28	D155N	29	D156N	30	D162N
31	D165N	32	D172N	33	D174N	34	D205N	35	D212N
36	D223N	37	D225N	38	D226N	39	D243N	40	D244N
41	D245N	42	D246N	43	D251N	44	D252N	45	D255N
46	D261N	47	D263N	48	D265N	49	D266N	50	D271N
51	D274N	52	D306N	53	D311N	54	D315N	55	D325N
56	D331N	57	D332N	58	D343N	59	D346N	60	D351N
61	D356N	62	D364N	63	D365N	64	D371N	65	D411N
66	D412N	67	D413N	68	D423N	69	D431N	70	D432N
71	D445N	72	D446N	73	D452N	74	D454N	75	D455N
76	D462N	77	D464N	78	D465N	79	D466N	80	D503N
81	D506N	82	D516N	83	D523N	84	D526N	85	D532N
86	D546N	87	D565N	88	D606N	89	D612N	90	D624N
91	D627N	92	D631N	93	D632N	94	D645N	95	D654N
96	D662N	97	D664N	98	D703N	99	D712N	100	D723N

101	D731N	102	D732N	103	D734N	104	D743N	105	D754N
106	D023I	107	D025I	108	D026I	109	D031I	110	D032I
111	D036I	112	D043I	113	D047I	114	D051I	115	D053I
116	D054I	117	D065I	118	D071I	119	D0721	120	D073I
121	D074I	122	D114I	123	D115I	124	D116I	125	D122I
126	D125I	127	D131I	128	D132I	129	D134I	130	D143I
131	D145I	132	D152I	133	D155I	134	D156I	135	D162I
136	D165I	137	D172I	138	D174I	139	D205I	140	D212I
141	D223I	142	D225I	143	D226I	144	D243I	145	D244I
146	D245I	147	D246I	148	D251I	149	D252I	150	D255I
151	D261I	152	D263I	153	D265I	154	D266I	155	D271I
156	D274I	157	D306I	158	D311I	159	D315I	160	D325I
161	D331I	162	D332I	163	D343I	164	D346I	165	D351I
166	D356I	167	D364I	168	D365I	169	D371I	170	D411I
171	D412I	172	D413I	173	D423I	174	D431I	175	D432I
176	D445I	177	D446I	178	D452I	179	D454I	180	D455I
181	D462I	182	D464I	183	D465I	184	D466I	185	D503I
186	D506I	187	D516I	188	D523I	189	D526I	190	D532I
191	D546I	192	D565I	193	D606I	194	D612I	195	D624I
196	D627I	197	D631I	198	D632I	199	D645I	200	D654I
201	D6621	202	D664I	203	D703I	204	D712I	205	D723I
206	D731I	207	D732I	208	D734I	209	D743I	210	D754I

Appendix E. - CTCSS Table

CTCSS CHART (Hz)

Number	Frequency								
1	67.0	2	69.3	3	71.9	4	74.4	5	77.0
6	79.7	7	82.5	8	85.4	9	88.5	10	91.5
11	94.8	12	97.4	13	100	14	103.5	15	107.2
16	110.9	17	114.8	18	118.8	19	123.0	20	127.3
21	131.8	22	136.5	23	141.3	24	146.2	25	151.4
26	156.7	27	159.8	28	162.2	29	165.5	30	167.9
31	171.3	32	173.8	33	177.3	34	179.9	35	183.5
36	186.2	37	189.9	38	192.8	39	196.6	40	199.5
41	203.5	42	206.5	43	210.7	44	218.1	45	225.7
46	229.1	47	233.6	48	241.8	49	250.3	50	254.1

Appendix F.- NOAA Weather Radio Frequency List (US, CAN)

Channel Number	RX Frequency	Weather Channel	Channel Number	RX Frequency	Weather Channel
	MHz			MHz	
117	162.550	WX1	123	162.525	WX 7
118	162.400	WX 2	124	161.650	WX 8
119	162.475	WX 3	125	161.775	WX 9
120	162.425	WX 4	126	161.750	WX 10
121	162.450	WX 5	127	162.000	WX 11
122	162.500	WX 6			

Disclaimer

The accuracy and completeness of the contents are sought in the process of compilation, but we do not bear any responsibility for the possible errors or omissions. With the continuous development of technology, we reserve the right to change the design and specification of the product without notice. No copy, modification, translation and dissemination of this handbook may be made in any form without the prior written authorization of our department.

