GRANT OF EQUIPMENT AUTHORIZATION

TCB

Certification

Issued Under the Authority of the Federal Communications Commission

By:

Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue Sunnyvale, CA 94089 Date of Grant: 04/25/2025

Application Dated: 04/25/2025

PO FUNG ELECTRONIC (HK) INTERNATONAL GROUP COMPANY LIMITED

Room 1508, 15/F, Office Tower II, Grand Plaza, 625 Nathan Road Kowloon, Hong Kong

Attention: Peter Wang,

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: 2AJGM-DM32UV

Name of Grantee: PO FUNG ELECTRONIC (HK)

INTERNATONAL GROUP COMPANY

LIMITED

Equipment Class: Scanning Receiver

Notes: Digital Radio

Frequency Output Frequency Emission

Grant Notes FCC Rule Parts Range (MHZ) Watts Tolerance Designator

15B 108.0 - 136.0

15B 136.0 - 174.0

15B 400.0 - 470.0

TCB

GRANT OF EQUIPMENT AUTHORIZATION

TCE

Certification

Issued Under the Authority of the Federal Communications Commission

By:

Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue Sunnyvale, CA 94089 Date of Grant: 04/25/2025

Application Dated: 04/25/2025

PO FUNG ELECTRONIC (HK) INTERNATONAL GROUP COMPANY LIMITED

Room 1508, 15/F, Office Tower II, Grand Plaza, 625 Nathan Road Kowloon, Hong Kong

Attention: Peter Wang,

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: 2AJGM-DM32UV

Name of Grantee: PO FUNG ELECTRONIC (HK)

INTERNATONAL GROUP COMPANY

LIMITED

Equipment Class: Licensed Non-Broadcast Transmitter Held to

Face

Notes: Digital Radio

Grant Notes	FCC Rule Parts	Frequency <u>Range (MHZ)</u>	Output <u>Watts</u>	Frequency <u>Tolerance</u>	Emission <u>Designator</u>
EF	90	136.0 - 174.0	5.0	2.5 PM	11K0F3E
EF ES	90	136.0 - 174.0	5.0	2.5 PM	7K60F1D
EF ES	90	136.0 - 174.0	5.0	2.5 PM	7K60F1E
EF	90	400.0 - 406.0	5.0	2.5 PM	11K0F3E
EF ES	90	400.0 - 406.0	5.0	2.5 PM	7K60F1D
EF ES	90	400.0 - 406.0	5.0	2.5 PM	7K60F1E
EF	90	406.1 - 470.0	5.0	2.5 PM	11K0F3E
EF ES	90	406.1 - 470.0	5.0	2.5 PM	7K60F1D
EF ES	90	406.1 - 470.0	5.0	2.5 PM	7K60F1E

Output power listed is rated conducted. This device must be restricted to work-related operations only in an occupational/controlled RF exposure environment and must operate with a duty factor not exceeding 50%. This transmitter may operate with the antenna(s) documented in this filing in Push-to-Talk and body-worn configurations. RF exposure compliance is limited to the specific belt-clip and accessory configurations as documented in this filling, the separation distance between user and the device or its antenna shall be at least 2.5 cm. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with occupational/controlled Exposure limit and requirements. A label, as described in this filling, must be displayed on the device to direct users to specific training information for meeting occupational exposure requirements. The

highest reported SAR levels for Head and Body-worn accessories are 2.47 W/kg and 5.99 W/kg, respectively when operating at 50% Duty Cycle.

- EF: This device may contain functions that are not operational in U.S Territories except as noted in the filing. This grant has extended frequencies as noted in the filing and Section 2.927(b) applies to this authorization.
- ES: This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth.